

# 3D: A H2O2O Project for the Demonstration of the DMX<sup>TM</sup>Process

Paul Broutin\*, Bernard Petetin, Xavier Courtial, Maxime Lacroix

IFP Energies nouvelles, ArcelorMittal, Axens, TOTAL

18/09/2019 Kyoto

PCCC-5



- Context
- DMX<sup>TM</sup> Process
- 3D Project
  - 3D in a Nutshell
  - Objectives
  - Synopsis
- 3D Pilot Plant



# Context : GHG Mitigation in Industry

In IEA 2DS, CCS in Industry is supposed to deliver 12 % of CO<sub>2</sub> emission cuts by 2050



 Ambition of the European Union: Reduction from 1.7 tons of CO<sub>2</sub> per tonne of steel to less than 1.2 in 2030 <u>only reachable via CCS</u>





000

°°



Rich amine

CO<sub>2</sub> rich

Lean amine

amine

#### **Performances**

CO2

1) Very high cyclic capacity (4 times MEA)

CO2

0

phase

separation

absorption

DMX

Solvent

- 2) Solvent very stable  $\rightarrow$  CO<sub>2</sub> may be produced in Pressure (up to 6 barg)
- 3) No corrosion observed with Carbon Steel



CO<sub>2</sub> lean

phase

CO<sub>2</sub>rich phase

Flue Gas



Reboiler

# DMX Technology Development



COD DEMONSTRATION DUNKIRK

TRL 1

# Main Results of the OCTAVIUS Project (Coal Power Station Application)

Low Energy for solvent regeneration ( < 2.3 GJ/tCO2 @ 90 % capture rate / without any integration)</p>

Singh P. (IEAGHG), Van Swaaij W., Brilman D., Energy Efficient Solvents for CO2 Absorption from Flue Gas: Vapor Liquid Equilibrium and Pilot Plant Study, Energy Procedia 37 (2013) 2021-2046, Oral présentation, GHGT-11, Kyoto, 2012.



## Results of the techno-economic evaluation

Process	Power Plant (without capture)	Power Plant + MEA (No LVC)	Power Plant + DMX <sup>TM</sup>
Net Elect. Production (MW)	743.5	559.0	592.2
Net Efficiency (%)	45.4	34.1	36.0
<b>Penalty (points)</b>		- 11.3	- 9.4

(Costs include CO<sub>2</sub> compression @ 110 bar)

Process	Power Plant (without capture)	Power Plant + MEA (No LVC)	Power Plant + DMX <sup>TM</sup>
CO <sub>2</sub> Emissions (ton/MWh)	0.76	0.08	0.08
C.O.E. (€/MWh) COE Increase (%)	61.2	99.0 + <b>61.9</b>	89.9 + <b>46.9</b>
CO <sub>2</sub> avoided Cost (€/ CO <sub>2</sub> ton)		56.5	42.5



## Main Results of the Valorco Project (Steel Mill Application)

- 3 cases considered: Power Station (PWS), Blast Furnace (BF), Blast Furnace with Top gas Recycle (TGR)
- 3 processes studied: MEA 30 wt%, MEA 40 wt%, DMX<sup>TM</sup> process



 $CO_2$  production cost (steam price = 21 $\notin$ /t)

#### Steam price impact on CO<sub>2</sub> production cost for DMX<sup>™</sup> process





- DMX Demonstration in Dunkirk
- H2020 project (call 2018 / topic LC-SC3-NZE-1)
- Project start-up : 01/05/2019
- Duration : 48 months
- Estimated eligible costs : 19.2 M€
- EU funding : 14.7 M€





- Demonstrate the DMX<sup>TM</sup> Process
- Prepare a first CCS large-scale demonstrator (> 1MtCO<sub>2</sub>/y)
- Study the CCS cluster 2035 Dunkirk-North Sea (10  $MtCO_2/y$ )











# 3D Pilot Plant

Capacity = 0.5 tCO<sub>2</sub> captured/hour



### Future location of the DMX pilot to be built @ ArcelorMittal steel mill in Dunkirk







# DMX Experimentation

- Permitting & FEED in progress
- Pilot Building to be achieved in June 2021
- Experimentation (September 2021 December 2022)
  - Phase 1 : Pilot Start-up (3 months)
    - Precommisioning
    - Commissioning
    - Test Run
  - Phase 2 : Parametric study ( 6 months)
    - Regeneration pressure and decantation pressure
    - Absorption pressure
    - CO<sub>2</sub> capture rate
    - Packing height
  - Phase 3 : 2 long run tests (2 x 3 months)
- BEMONSTRATION DUNKIRK
- Conditions defined after parametric studies

- Process performances evaluation : solvent flow rate, regeneration duty, CO effect.
- Operation conditions optimisation
- Models and simulation validation
- Process operability and solvent stability evaluation
- Corrosion effect

# DMX<sup>TM</sup>Process Commercialisation

- AXENS will commercialise the DMX<sup>TM</sup> process.
- Based on the pilot plant experimentation and the pre-FEED studies carried out within 3D, a first CCS demonstrator could be launched in Dunkirk with storage in Norway just after the end of this project (2022-2023).
- First application should be CO<sub>2</sub> capture on blast furnace gas but the DMX<sup>™</sup> process will be also commercialise for decarbonisation of flue gases from different origins (coal power stations, boilers, cement plants, petrochemical and refining units).





This project has received funding from the European Union's Horizon 2020 research and innovation programme under Grant Agreement No 838031.



Contact

3D DMX DEMONSTRATION DUNKIRK

Paul Broutin – IFPEN paul.broutin@ifpen.fr Phone: +33 4 37 70 26 97 Mobile: +33 6 45 50 22 87 



